

## technical data sheet






EN

### Product specifications

3-layer wood flooring	EN 14342 (Free Class)	DOP PQ2021-4
Dimensions	Plank	600-1900 x 190 x 14/ 3 mm
	Box	6 planken / 2,166 m <sup>2</sup> / 16,00 kg
	Nested lengths	5 full planks
	Pallet	55 boxen / 119,13 m <sup>2</sup> / 900 kg
Density	EN ISO 23996	+/- 650 kg/m <sup>3</sup>
Installation	ISO 24334	T&G (glued)
Top layer		3 mm European oak (Quercus Robur)
Grading		Rustical B+
Surface		Deeply brushed
Bevel		2-sided bevel
Gloss level	60°	6 %
Finishing		Oil
Warranty conditions	Residential use	20 years
	Commercial use	upon request
Application	EN 14342	Class 23



### Product properties

Property	Test method	min. req.	result
Indoor air certifications			A, REACH
Fire resistance	 EN 13501-1		Dfl-S1
Slip resistance	 EN 13893		DS (≥ 0.30)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m <sup>3</sup>	E1
Pentachlorofenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m <sup>2</sup> K/W	R = 0,10 m <sup>2</sup> K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: [www.lamett.eu](http://www.lamett.eu)



Rustic B+

EN

## Grading description

Texture	Deep brushed
Grading	Rustic
Colour variation	Medium - High
Sound knots	Allowed unlimited
Unsound knots	Partially filled
Bark	Exceptionally allowed, if suited from aesthetic point of view
Sapwood	Max 10%
End crack	Allowed unlimited, partially filled
Surface crack	Allowed limited, partially filled
Insect hole	Traces of insects allowed, insects not allowed
Decay	Not allowed
Blue/yellow stain	Allowed
Sound heart	Allowed
Machine marks	Not allowed



This picture is an indication of the grading as described.

## Grading description — 2 criteria

### Knots

Scale from (rigid) parquet without knots up to planks with more and larger knots



### Colour variation

From little colour variation/sapwood to bigger colour variation/sapwood

